

BPR-EMULSION PVC RESIN

QUALITY INDICATORS



Product Code	Degree of aggregation	Viscosity/ Mpa.s	Scrapping fineness/ μm	Volatiles%	Sifting %	Residue/ ppm
BPR-440	1350-1500	2000-4000	≤ 80	≤ 0.4	≥ 99	≤ 5.0
BPR-450	900-1000	4000-7000	≤ 80	≤ 0.4	≥ 99	≤ 5.0

PRODUCT FEATURES AND APPLICATION

Product Code	Characteristic	Application
BPR-440	It has low viscosity, excellent deaeration and excellent thermal stability.	Carpets, conveyor belts, steel belt products, artificial leather, toys, insulating sleeves, canvas, etc
BPR-450	With appropriate viscosity and excellent foaming properties, it is especially suitable for all kinds of chemical foam products.	Wallpaper, foamed leatherette, yoga mats, etc

Packing

This product is packaged in 20-25Kg bags



Storage

This product is non-toxic, non-corrosive solid powder, transportation according to non-dangerous goods treatment, should be strictly sun-proof, rain shower.

This product is stored in a cool and ventilated place, the shelf life is one year, after one year after the performance measurement, if there is no change, it can still be used.

Safety

This product is not classified as hazardous

Technical contact

For further technical information the contact details are showed below